

according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	ENERKOL
Other identifiers	UFI - 2A30-20KY-U003-VDYT
1.2 Relevant identified uses of the	substance or mixture and uses advised against
Use of the Sub- stance/Mixture	Solvent based adhesive
Recommended restrictions on use	For industrial use only.
1.3 Details of the supplier of the sa	afety data sheet
Company	Dunlop Service B.V.
Address	Heemst 2, 7892AL, Klazienaveen – Emmen, Netherlands +31 (0) 591 314 171
1.4 Emergency telephone number	
Emergency telephone number	 In case of poisoning: GBK-EMTEL International Tel.(24h):+49(0)6132/84463 (all languages) In case of transport accidents: Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 / GBK)
	National Poisons Information Centre (NPIC): 01 809 2566 (24 hours)
SECTION 2: Hazards identificat	tion

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Specific target organ toxicity - single ex-	H336: May cause drowsiness or dizziness.			



ENERKOL

Vers 2.0	ion	Revisior 04.10.20 Print Da 10.03.20)24 te:		DS Nun 000000 ⁻			e of last issue: 01.04.2022 e of first issue: 01.04.2022
	posure system		y 3, Central r	nerv	/ous			
	Long-te egory 2		nic) aquatic h	naza	ard, Cat	- H411:	Toxio	to aquatic life with long lasting effects.
2.2 L	.abel e	lements						
		ing (REG I pictograr	ULATION (E ms	C) :	No 1272	2/2008)		¥2
	Signal	word		:	Dange	r		
	Hazard	l statemer	nts	:	H225 H319 H336 H411	Causes se May cause	rious dro\	le liquid and vapour. eye irritation. vsiness or dizziness. life with long lasting effects.
	Supple Statem	emental Ha ients	azard	:	EUH06 drynes	66 s or cracking	g.	Repeated exposure may cause skin
	Precau	itionary st	atements	:	Preve	ntion:		
					P210 flames P233 P261 P273	and other ig Keep conta Avoid brea	gnitio ainer thing	n heat, hot surfaces, sparks, open n sources. No smoking. tightly closed. mist or vapours. o the environment.
					Respo	onse:		
							oam t	of fire: Use dry sand, dry chemical or o extinguish.
		na (petrole cetate	iponents wh eum), hydrotr			be listed on	the	abel:
	Additio	onal Labe	elling					
	EUH20)8		den	e)bis[pl	nenol] and 4		-(1,1-dimethylethyl)phenol, 4,4'-(1- nylphenol, Rosin, dodecane-1-thiol. May

produce an allergic reaction.



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022	
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022	
	Print Date:			
	10.03.2025			

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Con	nnon	ents
001	ipon	CIICO

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreat- ed light	64742-49-0 926-605-8 01-2119486291-36- 0000	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 30 - < 50
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46- 0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49- 0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
Formaldehyde, polymer with 4- (1,1-dimethylethyl)phenol, 4,4'-(1- methylethylidene)bis[phenol] and	26022-00-4	Skin Sens. 1; H317	>= 0,1 - < 1



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

Rosin	8050-09-7	Skin Sens. 1; H317	>= 0.1 - < 1
	232-475-7	, -	- ,
	650-015-00-7		
	01-2119480418-32-		
	0000		
dodecane-1-thiol	112-55-0	Skin Corr. 1C; H314	>= 0,0025 - <
	203-984-1	Eye Dam. 1; H318	0,025
	01-2119491318-31-	Skin Sens. 1A; H317	
	0000	Aquatic Acute 1;	
		H400	
		Aquatic Chronic 1;	
		H410	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice :	If on clothes, remove clothes. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
If inhaled :	Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of unconsciousness bring patient into stable side posi- tion for transport.
In case of skin contact :	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician if irritation develops or persists.
In case of eye contact :	Flush eyes with water at least 15 minutes. Get medical atten- tion if eye irritation develops or persists.
If swallowed :	Do NOT induce vomiting. If accidentally swallowed obtain immediate medical attention. Rinse mouth with water. If conscious, drink fresh water. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks	: Causes serious eye irritation.
	May cause drowsiness or dizziness.
	Repeated exposure may cause skin dryness or cracking.



ENERKOL

Version 2.0	Revision Date: 04.10.2024 Print Date: 10.03.2025	SDS Number: 100000017101	Date of last issue: 01.04.2022 Date of first issue: 01.04.2022	

: No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Water mist Foam Dry powder Carbon dioxide (CO2)
Unsuitable extinguishing media	:	Do NOT use water jet.
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	May release toxic, irritating and/or corrosive gases. In case of fire, the following substance(s) may occur: Carbon monoxide
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
Further information	:	In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Remove all sources of ignition. Use personal protective equipment. Use breathing protection against the effects of fumes/dust/aerosol. Evacuate personnel to safe areas. Ensure adequate ventilation.	
----------------------	---	--	--

6.2 Environmental precautions

Environmental precautions	:	Prevent the material from reaching sewage system, holes and
		cellars.



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022	
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022	
	Print Date:			
	10.03.2025			

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Ensure adequate ventilation. Send for recovery or disposal in suitable containers.
-------------------------	---

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Avoid formation of dust and aerosols. Handle with care. Keep eye wash bottle available on working place. Avoid release to the environment. Take note of emission threshold. Use solvent-proof equipment. Ensure that suitable extractors are available on processing machines. Keep out of reach of children. Take precautionary measures against static discharges. Use only with adequate ventilation.
Advice on protection against fire and explosion	:	Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mix- tures in air. Highly volatile, flammable constituents are re- leased during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.
7.2 Conditions for safe storage, i	nc	luding any incompatibilities
Requirements for storage areas and containers	:	Use explosion-proof equipment. Keep tightly closed in a dry, cool and well-ventilated place. Do not freeze.
Further information on stor-	:	Store in a cool place. Heat will increase pressure and may

age conditions	lead to the container exploding.	·	,

Advice on common storage : Do not store together with oxidizing and self-igniting products.

7.3 Specific end use(s)



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

Specific use(s)

: No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
ethyl acetate	141-78-6	OELV - 8 hrs (TWA)	200 ppm 734 mg/m3	IE OEL		
		OELV - 15 min (STEL)	400 ppm 1.468 mg/m3	IE OEL		
		STEL	400 ppm 1.468 mg/m3	2017/164/EU		
	Further inform	nation: Indicative				
		TWA	200 ppm 734 mg/m3	2017/164/EU		
	Further inform	nation: Indicative	-			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC		
	Further inform	Further information: Indicative				
		OELV - 8 hrs (TWA)	500 ppm 1.210 mg/m3	IE OEL		
dodecane-1-thiol	112-55-0	OELV - 8 hrs (TWA)	0,1 ppm	IE OEL		
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis					

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef-	Value
			fects	
ethyl acetate	Workers	Eye contact	Local effects	
	Workers	Inhalation	Systemic, short-term	1468 mg/m3
	Workers	Inhalation	Systemic, long-term	734 mg/m3
	Workers	Inhalation	Local, short-term	1468 mg/m3
	Workers	Inhalation	Local, long-term	734 mg/m3
	Workers	Dermal	Systemic, long-term	63 mg/kg
acetone	Workers	Inhalation	Local, short-term	2420 mg/m3
	Workers	Inhalation	Systemic, long-term	1210 mg/m3
	Workers	Eye contact	Local effects	
	Workers	Dermal	Systemic, long-term	186 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Soil	0,148 mg/kg



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

	Predator	0,2 g/kg
	Fresh water sediment	1,15 mg/kg
	Fresh water	0,24 mg/l
	Sewage treatment plant	650 mg/l
	Marine water	0,024 mg/l
	Marine sediment	0,115 mg/kg
acetone	Soil	29,5 mg/kg
	Sewage treatment plant	100 mg/l
	Fresh water	10,6 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine water	1,06 mg/l
	Marine sediment	3,04 mg/kg

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection	: Tightly fitting safety goggles or equipment with better protec- tion
Hand protection Material	: Solvent-resistant gloves
Remarks	: Direct contact with the product must be avoided by organiza- tional measures.
	The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the pro- tective glove producer and this has to be observed. The gloves need to be disposed after the penetration time and replaced by new ones. Apply skin protectant before working with gloves to avoid skin
	swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from



ENERKOL

Version 2.0	Revision Date: 04.10.2024 Print Date: 10.03.2025	SDS Number:Date of last issue: 01.04.2022100000017101Date of first issue: 01.04.2022	
		Ansell or other suppliers (penetration time: 480 min).	
		For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Butyl rubber (minimum thickness: 0.7 mm; penetration time 15 min)	
		As protection from splashes gloves made of the follow- ing materials are suitable: Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs	
		After contact with the chemical preparation, take the dispos able nitrile glove off immediately and put on a new disposat nitrile glove.	
Skin a	and body protection	: Protective clothing	
Resp	iratory protection	 Use respiratory protection unless adequate risk manageme measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Ensure that suitable extractors are available on processing machines. 	- ′)
Fil	ter type	: Organic vapour type or equipment with better protection (A	.)
Prote	ctive measures	 Keep away from food, drink and animal feedingstuffs. Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately. Provide adequate ventilation. 	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	black



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Vers 2.0	sion	Revision Date: 04.10.2024 Print Date: 10.03.2025		S Number: 0000017101	Date of last issue: 01.04.2022 Date of first issue: 01.04.2022
	Odour Odour Threshold		:	characteristic	
			:	is not determined	I
	Melting point/freezing point		:	is not determined	l
	Boiling	point/boiling range	:	77 °C	
	Flash p	oint	:	-20 °C	
	Auto-ig	nition temperature	:	is not determined	l
	Decom	position temperature	:	Not applicable	
	pН		:	substance/mixtur	e is non-polar/aprotic
	Viscosi Visc	ty osity, dynamic	:	3.500 mPa.s (20	°C)
	Visc	osity, kinematic	:	> 20,5 mm2/s (40) °C)
	Solubili Wat	ty(ies) er solubility	:	not miscible or di	fficult to mix
	Partitio octanol	n coefficient: n- /water	:	no data available	
	Vapour	pressure	:	105 hPa (20 °C)	
	Density	,	:	0,86 g/cm³ (20 °C	
	Relative	e vapour density	:	is not determined	l
9.2	Other in	formation			
	Explosi	ves	:	Product is not expour/air mixture	plosive. However, formation of explosive es is possible.
	Evapor	ation rate	:	is not determined	l

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version 2.0	Revision Date: 04.10.2024 Print Date: 10.03.2025	SDS Num 10000001		Date of last issue: 01.04.2022 Date of first issue: 01.04.2022	
	ssibility of hazardous				
Haz	ardous reactions	: Deve	lops read	ly flammable vapours/fumes.	
10.4 Co	nditions to avoid				
Cor	nditions to avoid	: Heat	, flames a	nd sparks.	
10.5 Inc	ompatible materials				
Mat	erials to avoid	: No fu	urther relev	ant information available.	
	zardous decompositio decomposition if stored	-	as directed	l.	
SECTIC	ON 11: Toxicological	informatio	n		
11.1 Info	ormation on hazard cla	isses as defi	ined in Re	gulation (EC) No 1272/2008	
Αςι	ite toxicity ed on available data, th				
Cor	nponents:				
-	ohtha (petroleum), hyd te oral toxicity	-		350 mg/kg	
Acu	te inhalation toxicity		(Rat): > 2 sure time:		
Acu	te dermal toxicity	: LD50	(Rabbit):	> 2.000 mg/kg	
eth	yl acetate:				
	te oral toxicity	: LD50	Oral (Rat)	: 5.620 mg/kg	
Acu	te inhalation toxicity	Expos	(Rat): 22, sure time: atmospher		
Acu	te dermal toxicity	: LD50	Dermal (F	Rabbit): > 20.000 mg/kg	
Ski	n corrosion/irritation				

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.



ENERKOL

Version	Revision Date:
2.0	04.10.2024
	Print Date:
	10.03.2025

SDS Number: 100000017101 Date of last issue: 01.04.2022 Date of first issue: 01.04.2022

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Naphtha (petroleum), hydrotreated light:

Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): 3 mg/l
aquatic invertebrates		Exposure time: 48 Hours

ethyl acetate:

Toxicity to fish



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Vers 2.0	sion	Revision Date: 04.10.2024 Print Date: 10.03.2025		0S Number: 0000017101	Date of last issue: 01.04.2022 Date of first issue: 01.04.2022
				mg/l Exposure time: 96 Test Type: flow-th	
		/ to daphnia and other invertebrates	:	EC50 (Daphnia m Exposure time: 48 Test Type: static t	
12.2		tence and degradabil a available	ity		
12.3	Bioaco	cumulative potential			
	Compo	onents:			
	ethyl a Partitio octanol	n coefficient: n-	:	log Pow: > 0,66 - pH: 7 GLP: no	< 0,73 (25 °C)
	aceton	e:			
	Partitio octanol	n coefficient: n- /water	:	log Pow: -0,24	
		ane-1-thiol: n coefficient: n- /water	:	log Pow: 6,18	
12.4	Mobili	ty in soil			
	Produc				
	Mobility		:	Medium: Soil Remarks: Do not bodies or sewage	allow product to reach ground water, water system.
12.5	i Result	s of PBT and vPvB as	sse	ssment	
	Produc	<u>::</u>			
	Assess	ment	:	to be either persis	ixture contains no components considered stent, bioaccumulative and toxic (PBT), or d very bioaccumulative (vPvB) at levels of



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022	
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022	
	Print Date:			
	10.03.2025			

12.6 Endocrine disrupting properties

Ρ	r	n	d		c	t	•	
Γ.		U	u	u	C	L		

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Ρ

roduct	 Do not dispose of with domestic refuse. Do not dispose of waste into sewer. Hand over to disposers of hazardous waste. The generation of waste should be avoided or minimized wherever possible. Incinerate under controlled conditions in accordance with all local and national laws and regulations. Disposal must be made according to official regulations.
	These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).
	Waste accruing during application:08 04 09*waste adhesives and sealants containing or- ganic solvents or other dangerous substances08 04 10waste adhesives and sealants other than those mentioned in 08 04 09
	Waste accruing during cleaning:08 04 11*adhesive and sealant sludges containing or-ganic solvents or other dangerous substances08 04 12adhesive and sealant sludges other thanthose mentioned in 08 04 11
	Waste packaging:15 01 01paper and cardboard packaging15 01 02plastic packaging15 01 04metallic packaging15 01 10*packaging containing residues of or contaminated by dangerous substances.



ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024 Print Date: 10.03.2025	100000017101	Date of first issue: 01.04.2022

Contaminated packaging

: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN	number	or ID	number
---------	--------	-------	--------

	ADR	:	UN 1133
	RID	:	UN 1133
	IMDG	:	UN 1133
	ΙΑΤΑ	:	UN 1133
14.	2 UN proper shipping name		
	ADR	:	ADHESIVES
	RID	:	ADHESIVES
	IMDG	:	ADHESIVES (HYDROCARBONS, C6-C7)
	IATA	:	Adhesives
14.	3 Transport hazard class(es)		
	ADR	:	3
	RID	:	3
	IMDG	:	3
	ΙΑΤΑ	:	3
14.	4 Packing group		
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks		III F1 30 3 (D/E) This product is eligible to ship using the Limited Quantity ex- ception when packed in inner packaging under 5 L and outer packaging up to 30 kg.
	RID		

Packing group	:	111
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

IMDG Packing group Labels EmS Code	:	III 3 F-E, S-D
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: : :	366 Y344 III Flammable Liquids
IATA_P (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids

14.5 Environmental hazards

ADR Environmentally hazardous	:	yes
RID Environmentally hazardous	:	no
IMDG Marine pollutant	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High : Compliant



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	100000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

Concern for Authorisation (SVHC, Article 59)			
Regulation (EC) 2024/590 on substances that de the ozone layer	eplete	:	Compliant
Regulation (EU) 2019/1021 on persistent organic tants (recast)	pollu-	:	Compliant
RoHS: 2011/65/EU, Restriction of Hazardous Su es	bstanc-	:	Compliant
Council Regulation (EC) No 111/2005 laying dow for the monitoring of trade between the Commun third countries in drug precursors		:	Neither banned nor restricted
Regulation (EU) No 649/2012 of the European P ment and the Council concerning the export and of dangerous chemicals		:	Not applicable
Regulation (EU) 2019/1148 on the marketing and explosives precursors	d use of	:	acetone
REACH - List of substances subject to authorisat (Annex XIV)	tion	:	Compliant
Regulation (EU) 2019/1148 on the marketing and precursors	d use of	expl	losives
This product is regulated by Regulation (EU) 201 transactions, and significant disappearances and ported to the relevant national contact point.			
Seveso III: Directive 2012/18/EU of the Europe- an Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FL	AMMABLE LIQUIDS
	E2	ΕN	IVIRONMENTAL HAZARDS
imum Qualifying Quantity of Lower Tier Requi	rement :	:200)t

Minimum Qualifying Quantity of Lower Tier Requirement :200 t Maximum Qualifying Quantity of Higher Tier Requirement :500 t

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 77,75 %



ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:TSCA: All substances listed as active on the TSCA inventory				
	•			
AIIC	:	On the inventory, or in compliance with the inventory		
DSL	:	All components of this product are on the Canadian DSL		
KECI	:	On the inventory, or in compliance with the inventory		
PICCS	:	On the inventory, or in compliance with the inventory		
IECSC	:	On the inventory, or in compliance with the inventory		
REACH	:	On the inventory, or in compliance with the inventory		

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319 :	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H400	:	Very toxic to aquatic life.
H410 :	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations



according to Regulation (EC) No. 1907/2006, as amended

ENERKOL

Version 2.0	Revision Date: 04.10.2024 Print Date: 10.03.2025		S Number: 0000017101	Date of last issue: 01.04.2022 Date of first issue: 01.04.2022		
Aqu	atic Acute		Short-term (acute)	aquatic hazard		
	atic Chronic	÷	: Long-term (chronic) aquatic hazard			
	Tox.	:	Aspiration hazard			
	Dam.	:	Serious eye damage			
Éye		:	: Eye irritation			
	ı. Liq.	:	: Flammable liquids			
Skin	Corr.	:	Skin corrosion			
Skin	Sens.	:	Skin sensitisation			
STOT SE		:	Specific target organ toxicity - single exposure			
2000/39/EC		:	Europe. Commission Directive 2000/39/EC establishing a first			
			list of indicative occupational exposure limit values			
2017/164/EU		:		ion Directive 2017/164/EU establishing a		
				tive occupational exposure limit values		
IE OEL		:		emical Agents and Carcinogens with Occu-		
			• •	Limit Values - Code of Practice, Schedule 1		
			and 2			
2000/39/EC / TWA			Limit Value - eight			
	7/164/EU / STEL	:	Short term exposu			
	7/164/EU / TWA	:	Limit Value - eight			
	EL / OELV - 8 hrs (TWA)	:		osure limit value (8-hour reference period)		
-	EL / OELV - 15 min	:		osure limit value (15-minute reference peri-		
(STE	= -)		od)			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Re-



ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

striction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

: This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Modified data compared to the previous version

The following sections have been updated:

- Section 1
- Section 2
- Section 3
- Section 4
- Section 5
- Section 6
- Section 7
- Section 8
- Section 9
- Section 10
- Section 11
- Section 12
- Section 14
- Section 15
- Section 16

Contact Point

: Prepared by: Global Regulatory Department EU-MSDS@hbfuller.com

Classification	of the	mixture:
olussilloution		IIIIALUI C.

Classification procedure:

		•
Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



ENERKOL

Version	Revision Date:	SDS Number:	Date of last issue: 01.04.2022
2.0	04.10.2024	10000017101	Date of first issue: 01.04.2022
	Print Date:		
	10.03.2025		

IE / EN